

FAST RESPONSE PRTs

Model 5622



Specifications

Temperature Range	–200°C to 350°C
Nominal R_{TPW}	100Ω
Sensor	Four "385" platinum wires
Calibrated Probe Accuracy (includes calibration uncertainty and short-term stability)	5622-05 and 5622-10: $\pm 0.04^\circ\text{C}$ at -200°C $\pm 0.04^\circ\text{C}$ at 0°C $\pm 0.09^\circ\text{C}$ at 200°C $\pm 0.09^\circ\text{C}$ at 300°C 5622-16 and 5622-32: $\pm 0.04^\circ\text{C}$ at -200°C $\pm 0.04^\circ\text{C}$ at 0°C $\pm 0.045^\circ\text{C}$ at 200°C $\pm 0.055^\circ\text{C}$ at 300°C
Uncalibrated DIN/IEC Conformity	DIN/IEC Class A; $\pm 0.15^\circ\text{C}$ at 0°C
Time Constant (63.2%)	From 0°C to 100°C : 5622-05: 0.4 seconds 5622-10: 1.5 seconds 5622-16: 3.0 seconds 5622-32: 10 seconds (90%)
Immersion Depth	5622-05: 10 mm (0.4") 5622-10: 20 mm (0.8") 5622-16: 32 mm (1.25") 5622-32: 64 mm (2.5")
Thermal EMF	20 mV at 350°C
Sheath	316 SST 5622-05: 100 x 0.5 mm (4" x 0.02") 5622-10: 100 x 1.0 mm (4" x 0.04") 5622-16: 200 x 1.6 mm (8" x 0.06") 5622-32: 200 x 3.2 mm (8" x 0.13")
Cable	PVC, 4-wire cable, 2 meters long, 90°C max temp

Fast Response PRTs

Model 5622

- Time constants as fast as 0.4 seconds
- Available as DIN/IEC Class A PRTs or with ITS-90 calibration
- Small probe diameters ranging from 0.5 mm to 3.2 mm

For special temperature measurement applications requiring fast response or short immersion over a wide temperature range, Hart's new 5622 series PRTs are the perfect solution.

Made by Netsushin, one of the world's leading PRT manufacturers, this series includes four models with stainless steel sheaths ranging from 0.5 to 3.2 mm (0.02" to 0.125") in diameter. Because these high-quality wire-wound sensors come in small packages, heat transfer to the sensors occurs quickly. Time constants from 0°C to 100°C are as fast as 0.4 seconds.

Immersion requirements for these probes is also a plus, ranging from just 10 mm to 64 mm (0.4" to 2.5"), depending on the model. Getting into shallow or tight places is not a problem. And because these probes can handle temperatures from -200°C to 350°C , they're more versatile than most thermistors.

Model 5622 PRTs come with two calibration options. Uncalibrated, each of these probes conforms to DIN/IEC Class A re-

quirements with accuracy of $\pm 0.15^\circ\text{C}$ at 0°C and $\pm 0.55^\circ\text{C}$ at 200°C and -200°C . Alternatively, any Model 5622 PRT may be purchased with a Model 1922-4-N ITS-90 Comparison Calibration, which includes seven points from -197°C to 300°C . With calibration, short-term accuracies are achieved as good as $\pm 0.04^\circ\text{C}$ at 0°C .

Readout options for the Model 5622 PRTs include Hart's Little Lord Kelvin and Little Lord Logger Handheld Thermometers (page 37) as well as the 1502A Tweener Thermometer (page 40). Each of these readouts will read your PRT as a standard DIN/IEC probe or as an individually calibrated PRT.

Whatever your thermometry requirements are, come to Hart. No one else offers a wider range of standards-quality reference thermometers than Hart.

Ordering Information

5622-05-X	Fast Response PRT, 0.5 mm (0.02")
5622-10-X	Fast Response PRT, 1.0 mm (0.04")
5622-16-X	Fast Response PRT, 1.6 mm (0.06")
5622-32-X	Fast Response PRT, 3.2 mm (0.13")
<i>All models come without calibration unless calibration purchased separately.</i>	
1923-4-N	Calibration, PRT Comparison, -196°C to 300°C
2601	Protective Case

X = termination. Specify "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522 Handheld Thermometers), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), or "S" (spade lugs).



See our calibration and data acquisition software packages on page 74.