

Series 7750i

Ruska Laboratory Air Data Test Set

Technical Data



Features

- High accuracy, RVSM compliant
- Accuracy to ± 2 feet 0.02 knots
- True differential sensor for airspeed (Qc)
- One year calibration interval
- Automatic zeroing
- Variety of Ps and Qc ranges available

For more than thirty years, we have provided high precision Air Data Test Sets (ADTS) to the aerospace industry, airframe and component manufacturers for testing avionics instrumentation used on a variety of aircraft from fixed-wing to rotary to the space shuttle. The Model 7750i Air Data Test Set represents the latest generation ADTS incorporating a unique quartz sensor having unequalled precision and long term stability with the latest pressure control technology. The Model 7750i ADTS provides high performance measurement and control of all air data parameters.

The Model 7750i is a laboratory ADTS for calibrating a wide variety of avionics instrumentation such as altimeters, airspeed indicators, rate of climb meters, Mach meters,

air data computers and engine-based control systems that rely on accurate control and measurement of pressure. The 7750i can be used to calibrate devices that are required to meet the Reduced Vertical Separation Minimal (RVSM) requirements, controlling altitude to within two feet (better than 0.003 in Hg) at sea level. Additionally, the 7750i provides precision rate control for both altitude and airspeed.

The Model 7750i is ideal for use in Automatic Test Equipment (ATE) systems. The seven-inch height (4U) allows easy integration into comprehensive test systems. Additionally, an IEEE-488 interface is provided for PC-based control. The 7750i can be set to emulate previous generation ADTS (Model 6610), eliminating the need to alter existing software.

Specifications

Automatic go to ground

Upon selecting the go to ground command, the 7750i safely controls the pressure to the current, local barometric pressure. The user can then disconnect the device under test (DUT) without exposing sensitive instruments to a potential pressure transient or shock.

Leak test mode

A separate mode is provided for performing leak checks prior to beginning an actual calibration.

Protecting the device under test

In order to protect the DUT, the operator can program high and low limit settings for:

- Altitude
- Airspeed
- Rate of climb
- Mach
- Negative Qc
- ARINC 565 envelope

Automatic volume characterization

The 7750i automatically tunes the controller into external volumes ranging from 80 to 1000 cubic centimeters (5 to 60 cubic inches). This allows a large degree of flexibility for the configuration of the test system and the type of aircraft and components to be tested. For component manufacturers, a large number of devices can be tested simultaneously on a single manifold.

Automatic zeroing

As with any instrument, regular zeroing is suggested to achieve maximum performance. This task is now automated and can be performed at the push of a button, or over the PC interfaces. The 7750i incorporates the vacuum sensor onboard; no separate or external vacuum gauges or sensors are required. In addition, only one vacuum pump is required to operate and zero the 7750i ADTS. Zeroing is performed in 30 to 45 minutes using the specified vacuum pump.

Avionics and pressure units

The Model 7750i displays the common avionics units including feet and meters for altitude, calibrated airspeed in knots, km/hr, and Mach with corresponding rate displays for each unit per minute. It can also display pressure units.

High performance for fixed-wing or rotary aircraft

Although the standard configuration offered is a Ps range of 32 in Hg and a Qc range of 68 in Hg, we also offer custom ranges. For example, for exclusive testing of rotary aircraft, a Qc range of 32 in Hg can be provided, increasing performance in the lower airspeed ranges. For other custom ranges please consult factory.

Mode	Absolute		Differential	
Precision ^a	From 25 % to 100 % of FS: 0.005 % of reading below 25 % FS: 0.005 % of 25 % FS			
Stability: Over 3 months	0.0019 % RDG/3 months		0.0019 % RDG/3 months	
Over 1 year	0.0075 % RDG/year		0.0075 % RDG/year	
Zeroing vacuum sensor	± 10 mTorr (1.33 Pa) @ 100 mTorr		N/A	
Control stability	0.001 % FS		0.001 % FS	
Control low limit ^b	0.3 in Hg abs. (10 mbar a)		0 in Hg in - Qc mode/0.3 inHg abs. in Pt mode	
Zero drift	<0.004 % FS/24 hr.		<0.004 % FS/24 hr.	
Rate of climb	0 to 15,240 m (50,000 ft)/min		N/A	
Rate of climb tolerance	1 % of commanded to 15,240 m (50,000 ft)		N/A	
Standard load volume	80 cm ³ to 1,000 cm ³ (5 in ³ to 60 in ³)		80 cm ³ to 1,000 cm ³ (5 in ³ to 60 in ³)	
Mach	N/A		0 to 10.000 ^d	
Total uncertainty ^c (aeronautical units)	32 in Hg a	40 in Hg a	32 in Hg D	68 in Hg D
	Sea level ± 0.6 m (2 ft)	Sea level ± 0.6 m (2 ft)	50 ± 0.1 knots	50 ± 0.2 knots
	9,144 m (30,000 ft) ± 0.6 m (2 ft)	9,144 m (30,000 ft) ± 0.9 m (2 ft)	100 ± 0.05 knots	250 ± 0.04 knots
	18,288 m (60,000) ± 2.1 m (7 ft)	18,288 m (60,000) ± 2.4 m (8 ft)	250 ± 0.02 knots	500 ± 0.02 knots
Total uncertainty ^c (engineering units)	32 in Hg a	40 in Hg a	32 in Hg D	68 in Hg D
	32 ± 0.0030	40 ± 0.0037 inHg	0.5 ± 0.0005 in Hg	0.5 ± 0.001 in Hg
	30 ± 0.0025 in Hg	30 ± 0.0026 in Hg	16 ± 0.0013 in Hg	16 ± 0.0016 in Hg
	15 ± 0.0013 in Hg	15 ± 0.0014 in Hg	32 ± 0.0026 in Hg	32 ± 0.0027 in Hg
	5 ± 0.0008 in Hg	5 ± 0.0009 in Hg		68 ± 0.0055 in Hg

^a Precision is defined as the combined effect of linearity, repeatability and hysteresis throughout the operating temperature range. Some manufacturers use the word "Accuracy" in place of Precision," however the meaning is identical.

^b Requires vacuum pump to control 0 psig, or the vent mode can be used to obtain 0 psig.

^c Total uncertainty is defined as the two sigma combined uncertainty of linearity, hysteresis, repeatability, thermal effects one year drift stability and the uncertainty in the Ruska primary standard, which includes the uncertainty from NIST.

^d Limits can be set to prevent excessive mach.

Specifications

General		
Electrical power	90/260 V ac, 50/400 Hz, 150 W max.	
Temperature	Operating: 18 °C to 36 °C (64 °F to 97 °F) Storage: -20 °C to 70 °C (-4 °F to 158 °F)	
Humidity	Operating: 20 % to 75 % RH, non-condensing Storage: 5 % to 95 % RH, non-condensing	
Weight	20 kg (45 lb)	
Dimensions (H x W x D)	17.8 cm x 41.9 cm x 48.3 cm (7 in x 16.5 in x 19 in)	
Pressure medium	High purity nitrogen or dry, clean air	
Warm up time	3 hours	
Digital interface	IEEE-488.2 RS-232 Model 6610 emulation mode SCPI syntax	
Pneumatic connections	1/4 in FNPT on all ports. Adapters provided for AN6 and AN4	
Supply pressure	60 psi ± 5 psi (4 bar ± 0.5 bar)	
Supply vacuum	Minimum 50 liters per minute with auto-vent valve. Ultimate vacuum less than 1 mtorr	
Display		
	TFT active matrix color, 6.4 inch Display resolution: 1 ft, 0.1 m, 0.1 kn/hr, 0.00001 Mach	
Units		
Altitude	ft, meters	
Airspeed	knots, km/hr, Mach	
Pressure	Engineering units: inHg at 0 °C and 60 °F, kPa, bar, psi, inH ₂ O at 4 °C, and 25 °C, kg/cm ² , mmHg at 0°C, cmHg at 0°C, and cmH ₂ O at 4 °C and four user defined linear units of measure. Aeronautical units: feet, meters, knots, km/h, Mach	
Ranges	Ps	Qc
7750i-802	32	68
7750i-803	40	68
7750i-804	32	32
7750i-805	40	32
Control		
Rate control indication RoC: Rate of climb in all above units RtAS: Rate of airspeed in Knots or km/hr Total uncertainty expression: 2 Sigma Ps/32 inHg FS: RSS of 0.0091 % of Reading and 0.0008 inHg Ps/40 inHg FS: RSS of 0.0091 % of Reading and 0.0009 inHg Qc/32 inHg FS: RSS of 0.0091 % of Reading and 0.0007 inHg Qc/68 inHg FS: RSS of 0.0091 % of Reading and 0.0012 inHg		
Calibration		
One year interval is recommended. Use of primary standard such as the Model 2468 Pitot Static Gas Piston Gauge is recommended.		
Options		
Lines and fittings kit (supply and test lines) part number 7750-104 Vacuum pump .85 liter/minute capacity with auto-vent valve Filter and muffler National Instruments LabVIEW™ driver ISO 17025 accredited calibration certificate		

Fluke Calibration.
Precision, performance, confidence.™

Fluke Calibration
PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V.
PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:
In the U.S.A. (800) 443-5853 or
Fax (425) 446-5116
In Europe/M-East/Africa +31 (0) 40 2675 200 or
Fax +31 (0) 40 2675 222
In Canada (800)-36-FLUKE or
Fax (905) 890-6866
From other countries +1 (425) 446-5500 or
Fax +1 (425) 446-5116
Web access: <http://www.fluke.com>

©2010 Fluke Calibration.
Specifications subject to change without notice.
Printed in U.S.A. 8/2010 3833786A D-EN-N

**Modification of this document is not permitted
without written permission from Fluke Calibration.**

Cal Power

Via Acquanera, 29 22100 COMO
tel. 031.526.566 (r.a.) fax 031.507.984
info@calpower.it www.caltower.it